

1) Clear width in mm (indicative, depending on material thickness)

2) Mesh size centre to centre in mm

— Approximate weight in kg per 1 m² of hot-dip galvanized SP grating with edging strips

— 'N', 'T' see legend at bottom, page 11 —

Type	Number of bearing bars over 1000 mm wide	Clear width (1) Mesh size (2) (mm)	Bearing bar size: height/thickness																								
			20/3	25/2	25/3	25/4	5/5	30/2	30/3	30/4	30/5	35/2	35/3	35/4	35/5	40/2	40/3	40/4	40/5	50/3	50/4	50/5	60/4	60/5			
AA	30	31 x 33 34,3 x 38,1	15	20	18	24	N	32	38	20	28	37	45	23	32	42	52	26	36	48	58	44	58	72	69	85	
AC	30	31 x 45 34,3 x 50,8	14	19	16	23	N	30	37	19	27	36	44	22	31	41	51	25	35	46	57	43	57	71	68	84	
AX	30	31 x 71 34,3 x 76,2	13	18	16	22	S	29	36	18	26	35	43	21	30	40	49	24	34	45	56	—	56	70	—	—	
AE	30	31 x 96 34,3 x 101,6	12	18	15	22	N	29	35	18	26	34	42	20	30	39	49	23	34	45	56	42	56	69	66	82	
AI	30	31 x 14 34,3 x 19	19	24	21	28		36	43	24	32	41	47	27	36	47	56	—	40	52	63	—	—	—	—	—	
AK	30	31 x 19 34,3 x 24	17	22	20	26		34	41	22	31	39	48	25	35	45	54	—	—	50	61	—	—	—	—	—	
IX	68	12 x 71 14,8 x 76,2	26	37	32	46		—	—	37	55	—	—	43	64	—	—	49	73	—	—	—	—	—	—	—	
IE	68	12 x 96 14,8 x 101,6	25	37	31	46		—	—	37	54	—	—	43	63	—	—	49	72	—	—	—	—	—	—	—	
KK	46	19 x 19 22,1 x 24	22	31	25	37		53	—	31	43	61	—	35	49	69	—	39	55	77	—	—	—	—	—	—	
KA	46	19 x 33 22,1 x 38,1	20	28	24	34	N	45	—	28	40	53	—	32	46	61	—	36	52	N	69	—	65	85	—	102	—
KC	46	19 x 45 22,1 x 50,8	19	27	23	33	N	44	—	27	39	52	—	31	45	60	—	35	51	N	68	—	64	84	—	100	—
KX	46	19 x 71 22,1 x 76,2	18	26	22	32		43	—	26	38	51	—	30	44	59	—	34	51	67	—	63	83	—	99	—	
KE	46	19 x 96 22,1 x 101,6	18	26	22	32	N	42	—	26	38	50	—	30	44	58	—	34	50	N	66	—	62	82	—	99	—
MM	41	22 x 20 24,9 x 25	20	28	24	33		43	—	28	39	50	—	31	44	57	—	35	49	65	—	—	—	—	—	—	
MA	41	22 x 33 24,9 x 38,1	19	26	22	31		41	—	25	37	48	—	29	42	55	—	33	47	62	—	58	77	—	91	—	
MC	41	22 x 45 24,9 x 50,8	17	25	21	30		40	—	25	36	47	—	28	41	54	—	32	46	61	—	57	76	—	90	—	
MX	41	22 x 71 24,9 x 76,2	17	24	20	29		39	—	24	35	46	—	27	40	53	—	31	45	60	—	56	75	—	89	—	
ME	41	22 x 96 24,9 x 101,6	16	23	20	29		38	—	23	34	45	—	27	39	52	—	30	45	60	—	56	74	—	89	—	
BA	34	27 x 33 30,1 x 38,1	16	22	19	27		35	42	22	31	41	50	25	35	47	58	28	40	53	65	49	65	80	77	95	
BC	34	27 x 45 30,1 x 50,8	15	21	18	26	N	34	41	21	30	40	49	24	35	46	56	27	39	52	64	48	64	79	76	94	
BX	34	27 x 71 30,1 x 76,2	14	20	17	25		33	40	20	29	39	48	23	34	45	55	26	38	51	63	78	—	—	—	—	
BE	34	27 x 96 30,1 x 101,6	14	20	17	24		32	40	20	29	38	47	23	33	44	55	26	38	50	62	47	62	77	74	93	
EA	31	30 x 33 33,1 x 38,1	15	21	18	25		32	39	21	29	38	46	23	33	43	53	26	37	49	60	46	60	74	71	88	
EDF	31	30 x 27 33,1 x 33,8	—	21	18	25		33	40	21	29	38	47	24	34	44	54	27	38	50	61	—	61	75	—	88	
EC	31	30 x 45 33,1 x 50,8	14	20	17	24		31	38	20	28	37	45	22	32	42	52	25	36	48	59	45	59	73	70	87	
EX	31	30 x 71 33,1 x 76,2	13	19	16	23		30	37	19	27	36	44	22	31	41	51	24	35	47	58	—	58	72	—	—	
EE	31	30 x 96 33,1 x 101,6	13	18	15	22		29	36	18	26	35	43	21	31	41	50	24	35	46	57	43	57	71	68	85	
FA	27	35 x 33 38,3 x 38,1	—	19	16	22		29	35	19	26	34	41	21	30	39	47	24	33	44	53	41	53	66	63	78	
FC	27	35 x 45 38,3 x 50,8	—	18	15	21	N	28	34	18	25	33	40	20	29	38	46	23	32	42	52	40	52	64	62	77	
FX	27	35 x 71 38,3 x 76,2	—	17	14	20		27	33	17	24	32	39	19	28	37	45	22	31	41	51	39	51	63	—	—	
FE	27	35 x 96 38,3 x 101,6	—	15	14	20		26	32	16	23	31	38	19	27	36	44	21	31	41	50	38	50	63	60	75	

1) Clear width in mm (indicative, depending on material thickness)

2) Mesh size centre to centre in mm

— Approximate weight in kg per 1 m² of hot-dip galvanized SP grating with edging strips

— 'N', 'T' see legend at bottom —

Type	Number of bearing bars over 1000 mm wide (mm)	Clear width (1) Mesh size (2) (mm)	Bearing bar size: height/thickness																					
			20/3	25/2	25/3	25/4	5/5	30/2	30/3	30/4	30/5	35/2	35/3	35/4	35/5	40/2	40/3	40/4	40/5	50/3	50/4	50/5		
GA	25	38x33 41,4 x 38,1	18	15	21	27	33	18	24	32	39	20	28	36	44	22	31	41	50	38	50	61	59	73
GC	25	38x45 41,4 x 50,8	17	14	20	26	32	17	23	31	37	19	27	35	43	21	30	40	49	37	49	60	58	72
GX	25	38x71 41,4 x 76,2	16	13	19	25	31	16	23	30	36	18	26	34	42	20	29	39	48	36	48	59	—	—
GE	25	38x96 41,4 x 101,6	15	13	19	24	30	15	22	29	36	17	25	34	41	20	29	38	47	—	47	58	56	70
CK	24	40x19 43,2 x 24	19	17	23	29	35	19	26	33	40	22	29	38	45	—	33	42	51	37	—	—	—	—
CA	24	40x33 43,2 x 38,1	17	15	20	26	32	17	24	31	37	19	27	35	43	22	30	40	48	36	48	59	57	70
CC	24	40x45 43,2 x 50,8	16	14	19	25	31	16	23	30	36	18	26	34	42	20	29	38	47	35	47	58	56	69
CX	24	40x71 43,2 x 76,2	15	13	18	24	30	15	22	29	35	17	25	33	41	20	28	37	46	34	46	57	—	—
CE	24	40x96 43,2 x 101,6	15	12	18	24	29	15	21	28	35	17	24	32	40	19	28	37	45	34	45	56	54	67
HMA	21	47x33 49,8 x 38,1	15	14	19	24	—	16	21	28	—	18	24	32	—	20	27	36	—	—	43	—	—	—
HMC	21	47x45 49,8 x 50,8	15	13	18	23	—	15	20	27	—	17	23	31	—	18	26	34	—	32	42	—	50	—
HMX	21	47x71 49,8 x 76,2	14	12	17	22	—	14	20	26	—	16	22	29	—	18	25	33	—	31	41	—	—	—
HME	21	47x96 49,8 x 101,6	13	11	16	21	—	13	19	25	—	15	22	29	—	17	25	33	—	31	40	—	48	—
HEA	16	63x33 66,3 x 38,1	13	12	15	20	24	13	18	23	27	15	20	26	31	16	22	29	35	27	35	42	41	50
HEC	16	63x45 66,3 x 50,8	12	11	14	19	22	12	17	22	26	14	19	25	30	15	21	28	34	26	34	41	40	49
HEX	16	63x71 66,3 x 76,2	11	10	13	18	21	11	16	21	25	13	18	24	29	14	20	27	33	25	33	40	—	—
HEE	16	63x96 66,3 x 101,6	11	9	13	17	20	11	15	20	24	12	17	23	28	14	20	26	32	24	32	40	38	47
ZC	17	59x45 62,2 x 50,8	—	—	15	20	23	13	18	23	27	—	—	—	—	—	—	—	—	—	—	—	—	—
ZD	17	59x60 62,2 x 65	—	—	15	20	23	13	18	23	27	—	—	—	—	—	—	—	—	—	—	—	—	—
ZE	17	59x96 62,2 x 101,6	—	—	14	19	22	12	17	22	26	—	—	—	—	—	—	—	—	—	—	—	—	—
ZY	17	59x127 62,2 x 132	—	—	13	17	20	11	15	20	24	—	—	—	—	—	—	—	—	—	—	—	—	—
AA-8x8	30	8x8* 34,3 x 38,1	—	—	—	—	—	31	40	—	—	—	—	—	—	29	39	51	—	47	61	—	—	—
Type offshore AE	30	13x96 ** 34,3 x 101,6	—	—	27	34	40	—	31	39	47	—	35	44	54	—	39	50	60	—	60	74	70	62
Type offshore CE	24	11x96 *** 43,2 x 101,6	—	—	25	31	37	—	28	35	41	—	31	39	47	—	35	44	52	—	52	63	87	75

* clear width = 8 x 8 mm with the safety profile welded underneath

** clear width = 13 x 96 mm with a round bar welded between the 5 mm strong bearing bars

*** clear width = 11 x 96 mm with two round bars welded between the bearing bars

Choice of the following materials:
steel quality S235JR to S355JR conforming with EN 10025

Special mesh patterns are also available on request.

Options for special versions:

- serrated S4 and S5 (all types in bearing bar thicknesses 2/3/4 and 5 mm except 20/2)
- serrated S6 (all types with 'T' in the name, twisted cross bars available in Ø 4,5 / 5 / 6 / 8 mm; smooth/round cross bars in Ø 4 / 5 / 6 mm)

All types with 'N' in the name are available in stainless steel 1.4301 (V2A) or 1.4571 (V4A) with smooth/round cross bars in Ø 4 mm.

The weight of the stainless steel grating is decreased of approx. 7% in comparison to the standard steel and galvanized grating.